

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number  
**WO 2005/068152 A3**

(51) International Patent Classification<sup>7</sup>: **B29C 44/12,**  
45/16, 45/14

(21) International Application Number:  
PCT/US2005/000038

(22) International Filing Date: 3 January 2005 (03.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/534,321 3 January 2004 (03.01.2004) US

(71) Applicant (for all designated States except US): **JOHN-  
SON CONTROLS TECHNOLOGY COMPANY**  
[US/US]; 650 Waverly, Holland, Michigan 49423 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SMITH, Nels, R.**

[US/US]; 10230 Springwood Drive, Zeeland, Michigan 49464 (US). **HANSEN, Scott, A.** [US/US]; 447 Pinewood Court, Holland, Michigan 49424 (US). **STOUT, Jeffrey, T.** [US/US]; 2050 Francis Avenue SE, Grand Rapids, Michigan 49507 (US). **BUTZ, Andrew** [US/US]; 2916 - 104th Avenue, Zeeland, Michigan 49464 (US). **FOX, Bart, W.** [US/US]; 4654 Majestic Vue, Zeeland, Michigan 49464 (US).


(74) Agent: **GUSTAFSON, Adam, M.; FOLEY & LARDNER LLP**, 777 East Wisconsin Avenue, Milwaukee, WI 53202 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

[Continued on next page]

(54) Title: **VEHICLE COMPONENT AND METHOD FOR MAKING A VEHICLE COMPONENT**

(57) Abstract: The invention is also directed to a method for forming a component for a vehicle. The method comprises forming a substrate in a mold by injecting a first resin (14) into a first cavity, reconfiguring a portion of the mold to form a second cavity, and injecting a second resin (20) into a second cavity; providing a flexible member (122) adjacent at least a portion of the substrate to form a cavity between the substrate and the flexible member; coupling at least a portion of the flexible member (122) to the substrate; and introducing a material (140) into the cavity after securing at least a portion of the flexible member (122) to the substrate. The flexible member (122) and the material introduced into the cavity form a cushioned region for the vehicle component



WO 2005/068152 A3



PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:  
10 November 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.